

**105**  
*Years*  
OF TRUST AND  
RELIABILITY

 **Eagle**<sup>®</sup>  
S I N C E 1 9 1 8

# TITAN

## Weighing Scale



TITAN-C



**Designed for rugged retail and industrial applications**

Weighing | Counting | Accumulation | Liter Conversion

  
**KANTAKING**<sup>®</sup>  
ACCURATE WEIGHT BRINGS PROFIT

KANTA KING TECHNOLOGIES PVT LTD.

Channel Partner

+91.9560915555

info@kantaking.com

C-25, 2nd Floor, DSIDC Complex, Kirti Nagar, New Delhi - 110015

**Model & Range Chart :**

| Model No. | Capacity | Division | Pan Size     | Display | MOC Housing | MOC Pan    |
|-----------|----------|----------|--------------|---------|-------------|------------|
| TITAN-C   | 5/7.5 kg | 0.5/1 g  | 250 x 195 mm | LCD     | ABS Plastic | SS 304 Pan |
| TITAN-C   | 10 kg    | 1 g      |              |         |             |            |
| TITAN-C   | 10/20 kg | 1/2 g    |              |         |             |            |
| TITAN-C   | 20/30 kg | 2/5 g    |              |         |             |            |

**Standard Features:**

- Light and compact table top weighing scale
- ABS cabinet
- SS 304 pan
- Level adjustable legs
- Spirit level indicator near the pan
- Lithium-ion battery operated
- RS232 port
- Power adaptor - 5 V, 1 A, with type C USB charging connector
- Big rear display equivalent to front display
- Multiple unit conversions
- Weighing, piece counting, accumulation, litre conversion modes
- Provision to connect with portable thermal printer

**Technical Specification:**

| Description                | Titan Table Top Weighing Scale                                       |
|----------------------------|--|
| Physical dimension         | 256.5 x 266.5 x 121 mm   |
| Net weight                 | 2.4 kg approx  |
| Weight sensor              | Aluminium loadcell   |
| Processor                  | STM 32 BIT ARM   |
| Key board                  | 5 keys   |
| Display type               | LCD  |
| No. of displays            | Dual display (Front & Back)  |
| Display size               | LCD - 128 x 32 mm with 25 mm digit height                            |
| Calibration method         | External calibration firmware based                                  |
| Power adaptor              | USB C Type<br>O/P : 5 V DC, 1 A<br>I/P : 100 V to 230 V AC, 47-63 Hz |
| Power adaptor cable length | 2.5 meter  |
| Operating temp.            | 0°C to 50°C  |
| Battery capacity           | Lithium ion, 7.4 V, 1200 mAh   |
| Battery backup             | Estimated time : 8-10 hrs (If the battery is fully charged)          |
| Communication Interface    | RS232  |
| RTC                        | Not available  |

**OPTIONAL:**

- 1) Portable 2 inch thermal receipt printer
- 2) Portable 2 inch thermal label printer


**Print Format:**

|  |  |
|--|--|
| <p>Header Line 1<br/>Header Line 2<br/>Header Line 3</p> <hr/> <p>Sr. No. : 1<br/>Gross Wt : 2.000 kg<br/>Tare Wt : 0.000 kg<br/>Net Wt : 2.000 kg<br/>Count : 0 PCS</p> <hr/> <p>Footer Line 1<br/>Footer Line 2<br/>Footer Line 3</p> <p>(Simple Weighing)</p> | <p>Header Line 1<br/>Header Line 2<br/>Header Line 3</p> <hr/> <p>Sr. No. : 1<br/>Weighting Details<br/>1) 2.000 kg<br/>2) 2.050 kg<br/>3) 1.900 kg<br/>4) 1.985 kg<br/>5) 2.000 kg<br/>6) 2.000 kg<br/>7) 2.015 kg<br/>Total - 13.95 kg</p> <hr/> <p>Footer Line 1<br/>Footer Line 2<br/>Footer Line 3</p> <p>(Accumulation Weighing)</p> |
|--|--|

**Features Gallery:**



\*Models and specifications are subject to change without any prior notification.



**KANTA KING TECHNOLOGIES PVT LTD.**  
Channel Partner

+91.9560915555  
info@kantaking.com  
C-25, 2nd Floor, DSIDC Complex, Kirti Nagar, New Delhi - 110015  
www.kantaking.com